

59, TS – ROADIE® – THE ULTIMATE CASE SERIES



59



TS

- Ultra strong, soft tread, flexible Elastomer wheel rolls easily over cords, thresholds and debris and offers a cushioned ride on uneven surfaces such as truck ramps, etc.
- Wheel features roller bearing for improved mobility; capable of taking excessive abuse
- Double ball raceways offer responsive swiveling action and durability, are sealed to protect bearings from dirt and debris; ensuring a smooth performance
- Heavy-duty caster yoke is stamped and formed from 3/16" cold rolled steel
- Optional Total-locking brake simultaneously locks both the swivel raceway and wheel
- Entire caster yoke is heat treated for a long, reliable service life
- Standard zinc-plated finish is attractive and corrosion resistant
- Features popular top plate patterns used on mobile cases
- 3/8" axle with Zerk grease fitting in axle for maintenance

| Wheel Diameter | Tread Width | Load Capacity | Bearing Type | Overall Height | 59 Series Swivel Caster Part # | Swivel Radius | TS Series Total-Locking Swivel Part # | Swivel Radius |
|----------------|-------------|---------------|--------------|----------------|--------------------------------|---------------|---------------------------------------|---------------|
| 4 | 1-3/8 | 500 | ROLLER | 5-25/64 | 59RD40SU49**YY | 4-1/16 | T5RD40SU49**YY | 3-7/8 |

| FASTENING SPECIFICATIONS | | | |
|--|--------------|------------------------|--------------------|
| <i>Replace ** in part # with desired plate code.</i> | | | |
| Plate Code | Overall Size | Bolt Hole Pattern | Mounting Bolt Size |
| 10 | 85MM X 95MM | 60MM X 80MM | 8MM |
| 17 | 4 X 4-1/2 | 2-5/8 X 3-5/8 TO 3 X 3 | 3/8 |

69/70 – BRASS-PLATED SERIES



69



70

Designed for the hotel and hospitality industry to handle continuous and rigorous use and provide easy-to-roll, cushioned, and quiet ride.

- Brass plated
- Shock absorbing
- Quiet operation
- Floor protection

| FASTENING SPECIFICATIONS | | | |
|--|--------------|--------------------------------|--------------------|
| <i>Replace ** in part # with desired plate or stem code.</i> | | | |
| Plate Code | Overall Size | Bolt Hole Pattern or Stem Type | Mounting Bolt Size |
| 17 | 4 x 4-1/2 | 2-5/8 X 3-5/8 SLOTTED TO 3 X 3 | 3/8 |

| Wheel Diameter | Tread Width | Wheel Type | Load Capacity | Bearing Type | 69 Series Swivel Caster Part # | 69 Series Swivel with Wheel Brake Part # | 70 Series Rigid Caster Part # | Color | Overall Height | Swivel Radius |
|----------------|-------------|---------------------|---------------|--------------|--------------------------------|--|-------------------------------|----------------|----------------|---------------|
| 8 | 2 | YOKE ONLY | | | 69ZZ80SZ8317YY | | | | 9-1/2 | 6 |
| | | THERMO-PRO™ (ROUND) | 550 | PREC. BB | 69TP80JX6017YY | 69TP80JX6017TY | 70TP80JX6017YY | GRAY ON GRAY | | |
| | | THERMO-PRO™ (FLAT) | 550 | PREC. BB | 69TP80JT6017YY | 69TP80JT6017TY | 70TP80JT6017YY | GRAY ON BEIGE | | |
| 8 | 2-1/2 | YOKE ONLY | | | 69ZZ80LZ8317YY | | | | 9-3/4 | 6-1/2 |
| | | ECO-RUBBER™ | 450 | PREC. BB | 69SN80UCP317YY | 69SN80UCP317TY | 70SN80UCP317YY | BLACK ON GRAY | | |
| | 2-3/4 | EVER-ROLL™ | 250 | PREC. BB | 69ER80BCP317YY | 69ER80BCP317TY | 70ER80BCP317YY | BLACK ON ZINC | | |
| | 3 | PNEUMATIC | 250 | BALL | 69FP8A4FP317YY | 69FP8A4FP317TY | 70FP8A4FP317YY | BLACK ON BRASS | | |
| | 3 | PNEUMATIC | 250 | BALL | 69FP8A4RP317YY | 69FP8A4RP317TY | 70FP8A4RP317YY | GRAY ON BRASS | | |