



## FH – CHARIOT™ – PREMIUM CHAIR AND EQUIPMENT SERIES



- Full heat treated raceway to enhance durability
- **Choices of:**
  - Gray and black non-marking neoprene rubber wheel
  - Black PolyFlexion™ wheel
- Wheels with precision bearings
- Brake option available
- **Available Fastening:**
  - Grip Ring Stem 7/16 x 7/8 (53)
  - 3/8" I. D. Hollow Kingpin (ZZ)

| Wheel Diameter | Tread Width | Wheel Type            | Load Capacity | Finishing Type | FH Series Swivel Caster Part # | Overall Height | Swivel Radius | Replace ** with desired fastening pattern.               |
|----------------|-------------|-----------------------|---------------|----------------|--------------------------------|----------------|---------------|--|
| 2              | 13/16       | GRAY RUBBER           | 75            | BRIGHT CHROME  | FH20GRC4953                    | 2-3/4          | 2             |  |
|                |             | BLACK RUBBER          |               |                | FH20BRC4953                    |                |               |  |
|                |             | BLACK POLYFLEXION™    |               |                | FH20BPC4953                    |                |               |  |
|                |             | GRAY RUBBER           |               | BLACK CHROME   | FH20GRB4953                    |                |               |  |
|                |             | BLACK RUBBER          |               |                | FH20BRB4953                    |                |               |  |
|                |             | BLACK POLYFLEXION™    |               |                | FH20BPB4953                    |                |               |  |
| 3              | 13/16       | GRAY RUBBER           | 110           | BRIGHT CHROME  | FH30GRC6053                    | 3-7/8          | 2-7/8         | 53 = 7/16 X7/8 GRIP RING<br>ZZ = 3/8 I.D. HOLLOW KINGPIN |
|                |             | BLACK RUBBER          |               |                | FH30GRC6053T*                  |                |               |  |
|                |             | BLACK POLYFLEXION™    |               |                | FH30BRC60ZZ                    |                |               |  |
|                |             | GRAY RUBBER           |               | BLACK CHROME   | FH30BPC60ZZ                    |                |               |  |
|                |             | BLACK RUBBER          |               |                | FH30GRB6053                    |                |               |  |
|                |             | BLACK POLYFLEXION™    |               |                | FH30BRB60ZZ                    |                |               |  |
| 3              | 13/16       | BLACK NEOPRENE RUBBER | 110           | BRIGHT CHROME  | FH30BPC60ZZ                    | 3-7/8          | 2-7/8         | 53 = 7/16 X7/8 GRIP RING<br>ZZ = 3/8 I.D. HOLLOW KINGPIN |
|                |             |                       |               |                | FH30BRB60ZZ                    |                |               |  |
|                |             |                       |               |                | FH30BPB60ZZ                    |                |               |  |
|                |             |                       |               |                | FH30ENC6053T                   |                |               |  |
|                |             |                       |               |                | FH30ENC6053                    |                |               |  |
|                |             |                       |               |                | FH30ENC60ZZ                    |                |               |  |
|                |             |                       |               |                | FH30ENC6053T                   |                |               |  |
|                |             |                       |               |                | FH30ENC60ZZT                   |                |               |  |

\*With brake

## P5/PT – POLIMED™ COMPOSITE POLYMER SERIES

**NEW**



P5



PT

- Modern attractive design, injection molded from reinforced nylon polymer
- Strong, lightweight, corrosion and chemical resistant
- Sealed precision bearings in raceway and wheel
- Non-marking
- Swivel, Total Lock and Directional Lock

| FASTENING OPTION  |                |                            |                     |                            |          |           |
|---|----------------|----------------------------|---------------------|----------------------------|----------|-----------|
| Replace ** in part # with desired plate or stem code.                   |                |                            |                     |                            |          |           |
| Plate   | Overall Size   | Bolt Hole Pattern          |                     | Mounting Bolt Size         |          |           |
| 06  | 2-3/8 X 3-5/8  | 1-3/4 X 2-7/8 SLOTTED TO 3 |                     | 5/16                       |          |           |
| Order modular stems installed with stem code - or uninstalled by part # |                |                            |                     | Permanently attached stems |          |           |
| Stem Code   | Size           | Stem Type                  | Modular Stem Part # | Stem Code                  | Size     | Stem Type |
| 68  | 1/2-13/1-1/2   | THREADED                   | S7STT68             | 67                         | 1/2-13X1 | THREADED  |
| 70  | 1/2-13 X 2-3/4 | THREADED                   | S7STT70             |                            |          |           |
| 91  | 7/16 X 1-3/8   | GRIP RING                  | S7STG91             |                            |          |           |
| 95  | .846 X 2-3/16  | GRIP RING                  | S7STG95             |                            |          |           |
| S1  | 1/2-13X4       | THREADED                   | S7STTS1             |                            |          |           |
| S2  | 5/8-11X4       | THREADED                   | S7STTS2             |                            |          |           |
| S3  | 3/4-10X6       | THREADED                   | S7STTS3             |                            |          |           |

\*For more fastening, please refer to modular stem caster

| Wheel Diameter | Tread Width | Wheel Type  | Load Cap. | P5 Series Swivel Caster Part# | Swivel Radius | PT Series Swivel Total-Lock Caster Part # | Swivel Radius | PD Series Swivel Directional-Lock Caster Part # | Overall Height |
|----------------|-------------|-------------|-----------|-------------------------------|---------------|---|---------------|---|----------------|
| 3              | 1-1/4       | THERMO-PRO™ | 250       | P5TP30G144**YY                | 2-3/4         | PTTP40G144**YY                            | 3-3/4         | PDTP30G144**YY                                  | 4-3/4          |
| 4              | 1-1/4       |             | 275       | P5TP40G144**YY                | 3-7/16        | PTTP40G144**YY                            | 4-7/16        | PDTP40G144**YY                                  | 5-3/4          |
| 5              | 1-1/4       |             | 300       | P5TP50G144**YY                | 4             | PTTP50G144**YY                            | 4-7/16        | PDTP50G144**YY                                  | 6-7/8          |
| 6              | 1-1/4       |             | 300       | PTTP60G144**YY                | 4-9/16        | PTTP60G144**YY                            | 4-9/16        | PDTP60G144**YY                                  | 7-11/16        |

Note: POLIMED™ caster is designed for perfectly smooth floor. It is not designed to take any shocks from uneven floor or ride.