




# Wheels: CAST IRON V-GROOVE

**Durable Superior Casters®**



- Cast iron V-groove wheels are made specifically for use on inverted angle iron track; they can also be used on flat surfaces.
- Strong durable wheels at an economical price.
- Each wheel has a precisely machined 90° V-groove with relief groove which enables load equalization.
- Tensile strength of 30,000 PSI.
- Temperature range: -45° F to 600° F.

Wheel Diameter	Tread Width	Hub Length	Load Capacity	Part Number	Groove Width	Replace ** with desired bearing code.	
						Plain Bore	Roller Bearings
3	1-1/4	1-5/8	300	VG30GT**	7/8	82,83	
3	1-1/2	1-5/8	350	VG30HT**	7/8	84	01,03
4	1-1/2	1-5/8	350	VG40HT**	7/8	84	01,03
4	2	2-3/16	600	VG40JT**	7/8	84	02,04,09,92
5	2	2-3/16	900	VG50JT**	7/8	84	02,04,09,92
6	2	2-3/16	1000	VG60JT**	7/8	84	02,04,09,92
6	2-1/2	2-3/4	2500	VG60KT**	7/8	85	23,25
6	2-1/2	3-1/4	2500	VG60QT**	7/8	85	24,26
6	3	3-1/4	3500	VG60LT**	7/8	85	24,26
6	3	3-1/4	3500	VG60LW**	1-3/8	85	24,26
8	2	2-3/16	1200	VG80JT**	7/8	84	02,04,09,92
8	2-1/2	2-3/4	2500	VG80KT**	7/8	85	23,25
8	2-1/2	3-1/4	2500	VG80QT**	7/8	85	24,26
8	3	3-1/4	3500	VG80LT**	7/8	85	24,26
8	3	3-1/4	3500	VG80LW**	1-3/8	85	24,26
10	3	3-1/4	3500	VG10LT**	7/8	85	24,26
10	3	3-1/4	3500	VG10LW**	1-3/8	85	24,26



Bore & Bearing Sizes														
Bearing Code	01	02	03	04	09	23	24	25	26	82	83	84	85	92
Bearing or Bore Type	Roller Bearings				Caged Roller Bearing	Roller Bearings				Plain Bore				3/4 Roller w/Bushing
Inner Diameter	5/8	5/8	3/4	3/4	3/4	1	1	1-1/4	1-1/4	3/8	1/2	1-3/16	1-15/16	1/2

# Wheels: MAXROK™ V-GROOVE



- Injection molded ultra-strong, glass filled nylon wheel has the same weight capacity of steel, yet incredibly light-weight.
- Rust free material makes this the perfect wheel for outdoor applications.
- 100% washable & steam cleanable; not effected by grease, oils, most chemicals & cleaning solutions, salt, brine & blood.
- Extreme impact strength and abrasion and compression resistance.
- Durometer: 85 Shore D (+/-5).
- Temperature range: -45° F to 250° F

Wheel Diameter	Tread Width	Hub Length	Load Capacity	Part Number	Replace ** with desired bearing code.			
					Plain Bore	Roller Bearings	Precision Bearings	Delrin Bearings
4	1-1/2	1-5/8	600	MV40HT**	84	01,03		56,57,11,12
4	2	2-3/16	800	MV40JT**	84	02,04,05,09,92	60, 6S	56,57,11,12

Bore & Bearing Sizes														
Bearing/Bore Code	01	02	03	04	05	09	11	12	56	57	60	6S	84	92
Bearing / Bore Type:	Roller Bearings				S.S. Roller Bearings	Caged Roller Bearing	1 PC Delrin Bearing	2 PC Delrin Bearings	Sealed Prec. BB	S.S. Sealed Prec. BB	Plain Bore	3/4 I.D. Roller Bearing w/Bushing		
Inner Diameter:	5/8	5/8	3/4	3/4	3/4	3/4	3/4	1/2	1/2	3/4	1/2	1/2	1-3/16	1/2