




## Durable Superior Casters®



- High modulus quality rubber tread vulcanized to aluminum core.
- Rounded balloon cushion tread offers the best shock absorbing cushioned ride available, easily rolls over debris and small obstructions (electrical cords, floor joints, etc), offers maximum floor protection, high impact strength and ultra quiet rolling operation.
- High modulus round tread minimizes surface friction and enables wheel to turn easily.
- Gray & black tread colors are available; gray tread is non-marking.
- To maximize roll-ability, we recommend using # 63 Sealed precision ball bearings with top hat bushings.
- Durometer: 60 Shore A (+/-5).
- Temperature range: -40° F to 180° F.

Wheel Diameter	Tread Width	Hub Length	Load Capacity	Part Number <i>Replace + with Color Code</i>	Color Code	Replace ** with desired bearing code.			
						Plain Bore	Precision Ball Bearings	Roller Bearings	Delrin Bearings
6	2	2-3/16	350	BC60J+**	X, Z	84	63, 72	02,04,05,09,92	56,57,11,12
8	2	2-3/16	450	BC80J+**		84	63, 72	02,04,05,09,92	56,57,11,12

Bore & Bearing Sizes												
Bearing/Bore Code	02	04	05	09	11	12	56	57	63	72	84	92
<b>Bearing / Bore Type:</b>	Roller Bearings		S.S. Roller Bearings	Caged Roller Bearing	1 Piece Delrin Bearing		2 PC Delrin Bearings		Prec. BB w/top hat bushings	S.S. Prec. BB w/top hat bushings	Plain Bore	3/4 I.D. Roller Bearing w/Stl. Bushing
<b>Inner Diameter:</b>	5/8	3/4	3/4	3/4	3/4	1/2	1/2	3/4	1/2	1/2	1-3/16	1/2



## Wheels: RUBBER MOLD-ON ALUMINUM



- Rubber tread vulcanized to aluminum core.
- Offers shock absorbing cushioned ride, rolls over debris, offers floor protection & quiet rolling operation.
- Aluminum core has a strong attractive appearance, is lightweight and is resistant to rust and corrosion.
- Gray & black tread colors are available; gray tread is non-marking.
- 8 x 1-1/2" wheel comes with offset hub for use on hand trucks.
- Durometer: 80 Shore A (+/-5).
- Temperature range: -40° F to 160° F.



Wheel Diameter	Tread Width	Hub Length	Load Capacity	Part Number	Color	Replace ** with desired bearing code.				
						Plain Bore	Ball Bearings	Precision Ball Bearings	Roller Bearings	Delrin Bearings
3.5	1-1/4	1-9/16	250	RA35GI43	Gray		43			
4	1-1/4	1-9/16	250	RA40GI43			43			
5	1-1/4	1-9/16	275	RA50GI43			43			
4	2	2-3/16	400	RA40JB**	Black	84		60	02,04,05,09,92	56,57,11,12
5	2	2-3/16	500	RA50JB**		84		60	02,04,05,09,92	56,57,11,12
6	2	2-3/16	550	RA60JB**		84		60	02,04,05,09,92	56,57,11,12
8	1-1/2	*2-1/4	500	RA80HB**		95	51,52,53,P1,P2,P3			
8	1-5/8	2	500	RA80PB**		95	51,52,53,P1,P2,P3			
8	2-5/8	2-3/16	600	RA80JB**		84	51,52,53,P1,P2,P3		02,04,05,09,92	56,57,11,12

\*Offset Hub

Bore & Bearing Sizes																			
Bearing/Bore Code	02	04	05	09	11	12	51	52	53	P1	P2	P3	56	57	43	63	84	92	95
<b>Bearing / Bore Type:</b>	Roller Bearings		S.S. Roller Bearings	Caged Roller Bearing	1 Piece Delrin Bearing		Ball Bearings			Precision Ball Bearing (Flanged)			2 PC Delrin Bearings		Annular Ball Bearing	Prec. BB w/top hat bushings	Plain Bore	3/4 I.D. Roller Bearing w/Stl. Bushing	Plain Bore
<b>Inner Diameter:</b>	5/8	3/4	3/4	3/4	3/4	1/2	1/2	5/8	3/4	1/2	5/8	3/4	1/2	3/4	3/8	1/2	1-3/16	1/2	1-3/8