



Wheels: ERGOLASTOMER™

Durable Superior Casters®



- Super strength solid cast polyurethane elastomer one piece design with mechanically locked glass filled nylon bearing collar, offers the best durability and performance of any elastomer type wheel on the market.
- Precision and tapered bearings for towline use.
- 100% washable, steam cleanable, chemical resistant.
- Extreme impact strength and abrasion and compression resistance, will not flat spot when used within capacity rating.
- Offers a smooth ergonomic ride; easy start up.
- Bearing collar disperses heat away from elastomer wheel.
- Color: Gray with black core / bearing collar.
- Durometer: 68 Shore D (+/-5).
- Temperature range: -50° F to 180° F.

Wheel Diameter	Tread Width	Hub Length	Load Capacity	Part Number	Replace ** with desired bearing code.				
					Plain Bore	Roller Bearings	Tapered Bearings	Sealed Precision BB	Delrin Bearings
4	2	2-3/16	1000	HU40JI**	84	02,04,05,09,92	73	6S,63,72	56,57,11,12
5	2	2-3/16	1400	HU50JI**	84	02,04,05,09,92	73	6S,63,72	56,57,11,12
6	2	2-3/16	1700	HU60JI**	84	02,04,05,09,92	73	6S,63,72	56,57,11,12
6	2-1/2	2-3/4	2200	HU60KI**				15,16	
8	2	2-3/16	2000	HU80JI**	84	02,04,05,09,92	73	6S,63,72	56,57,11,12
8	2-1/2	2-3/4	2300	HU80KI**				15,16	
8	3	3-1/4	3000	HU80LI**				15,16	
10	3	3-1/4	3200	HU10LI**				15,16	

Bore & Bearing Sizes								
Bearing/Bore Code	02	04	05	09	11	12	56	57
Bearing / Bore Type:	Roller Bearing		S.S. Roller Bearings	Caged Roller Bearing	1 PC Delrin Bearing		2 PC Delrin Bearings	
Inner Diameter:	5/8	3/4	3/4	3/4	3/4	1/2	1/2	3/4

Bearing/Bore Code	15	16	60	6S	63	72	73	83	84	90	92
Bearing / Bore Type:	Precision BB with Top Hats.	Sealed Prec. BB (Flanged)	S.S. Sealed Prec. BB (Flanged)	Sealed Prec BB w/top hats	S.S. Sealed Prec BB w/top hats	Tapered Bearing w/ top hats	Plain Bore	83 Plain Bore with bushing	3/4 I.D. Roller Bearing w/Stl. Bushing		
Inner Diameter:	3/4	5/8	1/2	1/2	1/2	1/2	1/2	1/2	1-3/16	3/8	1/2

Wheels: DURALASTOMER®



- Solid cast polyurethane elastomer one piece design eliminates bonding failures and is a very reliable and durable wheel.
- 100% washable & steam cleanable; not affected by grease, oils, most chemicals & cleaning solutions, brine & blood.
- Offers a smooth effortless ride, is non-marking and protects floors.
- Resists compression set or "flat spotting", has exceptional impact strength and is highly abrasion resistant.
- Color: Blue
- Durometer: 60 Shore D (+/-5).
- Temperature range: -50° F to 180° F.

Wheel Diameter	Tread Width	Hub Length	Load Capacity	Part Number	Replace ** with desired bearing code.			
					Plain Bore	Roller Bearings	Precision BB	Delrin Bearings
3	1-1/4	1-9/16	300	SU30GL**	83, 90			
4	1-1/4	1-9/16	400	SU40GL**	83, 90			
5	1-1/4	1-9/16	700	SU50GL**	83, 90			
4	2	2-3/16	750	SU40JL**	84	02,04,05,09,92	60,6S,72	56,57,11,12
5	2	2-3/16	900	SU50JL**	84	02,04,05,09,92	60,6S,72	56,57,11,12
6	2	2-3/16	1000	SU60JL**	84	02,04,05,09,92	60,6S,72	56,57,11,12
8	2	2-3/16	1000	SU80JL**	84	02,04,05,09,92	60,6S,72	56,57,11,12

See above for bearing specifications