



Durable Superior Casters®



- Injection molded, 30% glass filled nylon wheel; has the same weight capacity of steel, yet incredibly light-weight.
- 100% washable & steam cleanable; not affected by grease, oils, most chemicals & cleaning solutions, salt, brine & blood.
- Extreme impact strength, good abrasion and compression resistance, will not flat spot.
- Offers a smooth ergonomic ride; requires less effort to start up and maintain a rolling load.
- *New Sizes: 10 x 2 and 12 x 2. Perfect for mobile equipment use.
- Durometer: 85 Shore D (+/-5).
- Temperature range: -45° F to 250° F (up to 350° F, when used with all metallic bearings and high-temp grease).



| Wheel Diameter | Tread Width | Hub Length | Load Capacity | Part Number | Replace ** with desired bearing code. | | | |
|----------------|-------------|------------------|---------------|-------------|---------------------------------------|-----------------|--------------------|-----------------|
| | | | | | Plain Bore | Roller Bearings | Precision Bearings | Delrin Bearings |
| 2 | 1-13/16 | 1-27/32 | 900 | MA20IB** | 84 | 29 | | |
| 2.5 | 1-13/16 | 1-15/16 | 1000 | MA25IB** | 82,84 | 08 | | |
| 3 | 1-13/16 | 1-15/16 | 1200 | MA30IB** | 83,84 | 36 | 63 | 56,57 |
| 3.25 | 2 | 2-3/16 | 900 | MA34JB** | 84 | 02,04,05,09,92 | 60,6S,63,72 | 56,57,11,12 |
| 4 | 2 | 2-3/16 | 800 | MA40JB** | 84 | 02,04,05,09,92 | 60,6S,63,72 | 56,57,11,12 |
| 5 | 2 | 2-3/16 | 1000 | MA50JB** | 84 | 02,04,05,09,92 | 60,6S,63,72 | 56,57,11,12 |
| 6 | 2 | 2-3/16 | 1200 | MA60JB** | 84 | 02,04,05,09,92 | 60,6S,63,72 | 56,57,11,12 |
| 8 | 2 | 2-3/16 | 1400 | MA80JB** | 84 | 02,04,05,09,92 | 60,6S,63,72 | 56,57,11,12 |
| 10 | 2 | 2-3/16 (*2-3/64) | 800 (*400) | MA10JB** | *8 | 02,04,05,09,92 | 60,6S,63,72 | 56,57,11,12 |
| 12 | 2 | 2-3/16 (*2-3/64) | 800 (*400) | MA12JB** | *8 | 02,04,05,09,92 | 60,6S,63,72 | 56,57,11,12 |

| Bore & Bearing Sizes | | | | | | | | | | | | | | | | | | | | |
|-----------------------------|-----------------|----------------------|-------------|-----------------|----------------------|------------------------|-----------------|----------------------|---------------------------|--------------------------------|---------------------------|--------------------------------|------------|-----|-----|--|-----|-----|--------|-----|
| Bearing/Bore # | 02 | 04 | 05 | *8 | 08 | 09 | 11 | 12 | 29 | 36 | 56 | 57 | 60 | 6S | 63 | 72 | 82 | 83 | 84 | 92 |
| Bearing / Bore Type: | Roller Bearings | S.S. Roller Bearings | *Plain Bore | Roller Bearings | Caged Roller Bearing | 1 Piece Delrin Bearing | Roller Bearings | 2 PC Delrin Bearings | Sealed Prec. BB (Flanged) | S.S. Sealed Prec. BB (Flanged) | Sealed Prec BB w/top hats | S.S. Sealed Prec BB w/top hats | Plain Bore | | | 3/4 I.D. Roller Bearing w/Stl. Bushing | | | | |
| Inner Diameter: | 5/8 | 3/4 | 3/4 | *5/8 | 3/4 | 3/4 | 3/4 | 1/2 | 1/2 | 3/4 | 1/2 | 3/4 | 1/2 | 1/2 | 1/2 | 1/2 | 3/8 | 1/2 | 1-3/16 | 1/2 |

Wheels: ROKHARD™

NEW!



- Injection molded reinforced thermoplastic wheel has the same weight capacity of steel, yet incredibly light-weight and impact resistant.
- Hard tread and precision bearings; offer a smooth ergonomic ride, requires less effort to start up and maintain a rolling load.
- 100% washable & steam cleanable; has the best chemical resistance of any wheel, not affected by grease, oils, most chemicals & cleaning solutions, salt, brine & blood.
- Extreme impact strength, good abrasion and compression resistance, will not flat spot.
- Durometer: 65 Shore D (+/-5).
- Temperature range: -45° F to 250° F



| Wheel Diameter | Tread Width | Hub Length | Load Capacity | Part Number | Replace ** with desired bearing code. | | | |
|----------------|-------------|------------|---------------|-------------|---------------------------------------|-----------------|--------------------|-----------------|
| | | | | | Plain Bore | Roller Bearings | Precision Bearings | Delrin Bearings |
| 4 | 2 | 2-3/16 | 800 | HI40JB** | 84 | 02,04,05,09,92 | 60,6S,63,72 | 56,57,11,12 |
| 5 | 2 | 2-3/16 | 1000 | HI50JB** | 84 | 02,04,05,09,92 | 60,6S,63,72 | 56,57,11,12 |
| 6 | 2 | 2-3/16 | 1200 | HI60JB** | 84 | 02,04,05,09,92 | 60,6S,63,72 | 56,57,11,12 |
| 8 | 2 | 2-3/16 | 1400 | HI80JB** | 84 | 02,04,05,09,92 | 60,6S,63,72 | 56,57,11,12 |

| Bore & Bearing Sizes | | | | | | | | | | | | | | |
|-----------------------------|-----------------|----------------------|----------------------|------------------------|----------------------|---------------------------|--------------------------------|---------------------------|--------------------------------|------------|--|-----|--------|-----|
| Bearing/Bore Code | 02 | 04 | 05 | 09 | 11 | 12 | 56 | 57 | 60 | 6S | 63 | 72 | 84 | 92 |
| Bearing / Bore Type: | Roller Bearings | S.S. Roller Bearings | Caged Roller Bearing | 1 Piece Delrin Bearing | 2 PC Delrin Bearings | Sealed Prec. BB (Flanged) | S.S. Sealed Prec. BB (Flanged) | Sealed Prec BB w/top hats | S.S. Sealed Prec BB w/top hats | Plain Bore | 3/4 I.D. Roller Bearing w/Stl. Bushing | | | |
| Inner Diameter: | 5/8 | 3/4 | 3/4 | 3/4 | 3/4 | 1/2 | 1/2 | 3/4 | 1/2 | 1/2 | 1/2 | 1/2 | 1-3/16 | 1/2 |