



Durable Superior Casters®

NEW!



- Non-marking high grade thermo plastic elastomer tread chemically bonded to a polyolefin core
- Shock absorbing cushioned ride offers floor protection and quiet rolling operation.
- Excellent impact resistance & durability, will not flat spot.
- Maximum resistance to cleaning chemicals, acids, alcohols, water and is excellent for wash down applications.
- Gray & black tread colors are available; both are non-marking.
- 1-1/4 wide wheels come with annular bearings & 2 inch wide wheels come with a variety of bearings including dual row sealed precision bearings (48) that offer a smooth, easy rolling ergonomic ride.
- Durometer: 65 Shore A (+/-5).
- Temperature range: -45° F to 180° F.

Wheel Diameter	Tread Width	Hub Length	Load Capacity	Part Number <i>Replace + with Color Code</i>	Color Code	Replace ** with desired bearing code.			
						Plain Bore	Delrin Bearings	Roller Bearings	Ball Bearings
3	1-1/4	1-9/16	230	NM30GI43	I = Gray				43
3.5	1-1/4	1-9/16	250	NM35GI43					43
4	1-1/4	1-9/16	260	NM40GI43					43
5	1-1/4	1-9/16	325	NM50GI43					43
4	2	2-3/16	400	NM40J+84	I = Gray B = Black	84	11, 12, 56, 57	02, 04, 05, 09, 92	48, 60, 6S
5	2	2-3/16	500	NM50J+84		84	11, 12, 56, 57	02, 04, 05, 09, 92	48, 60, 6S
6	2	2-3/16	600	NM60J+84		84	11, 12, 56, 57	02, 04, 05, 09, 92	48, 60, 6S
8	2	2-3/16	700	NM80J+84		84	11, 12, 56, 57	02, 04, 05, 09, 92	48, 60, 6S

Bore & Bearing Sizes														
Bearing/Bore Code	02	04	05	09	11	12	43	48	56	57	60	6S	84	92
Bearing / Bore Type:	Roller Bearings		S.S. Roller Bearings	Caged Roller Bearing	1 Piece Delrin Bearing		Annular Ball Bearings	Dual Row Sealed Prec. Ball Bearings	2 PC Delrin Bearings		Sealed Prec. BB (Flanged)	S.S. Sealed Prec. BB (Flanged)	Plain Bore	3/4 I.D. Roller Bearing w/Stl. Bushing
Inner Diameter:	5/8	3/4	3/4	3/4	3/4	1/2	3/8	1/4	1/2	3/4	1/2	1/2	1-3/16	1/2

Wheels: ELASTORIDE™



- Elastoride™ wheels have a balloon cushion thermo rubber tread on a ultra durable mag style polyolefin core.
- Lightweight wheel with offset hub for use on hand trucks & dollies.
- Offers a shock absorbing cushioned ride, floor protection and quiet rolling operation.
- Excellent impact resistance & durability, will not flat spot.
- Ball Bearings & sealed precision ball bearings available.
- Color: black tread on gray core (Non-Marking).
- Durometer: 55 Shore A (+/-5).
- Temperature range: -40° F to 180° F.



OFFSET Wheels for Hand Trucks

Wheel Diameter	Tread Width	Offset Hub Length	Load Capacity	Black Tread Part #	Gray Tread Part #	Replace ** with Bearing Code.	
						Ball Bearings	Sealed Precision Ball Bearings
8	2	2-1/4	250	RT80JZ**	RT80JI**	51, 52, 53	P1, P2, P3
10	2	2-1/4	300	RT10JZ**	RT10JI**	51, 52, 53	P1, P2, P3

Bore & Bearing Sizes						
Bearing Code:	51	52	53	P1	P2	P3
Bearing Type:	Ball Bearings			Prec. Ball Bearings		
Inner Diameter	1/2	5/8	3/4	1/2	5/8	3/4