



- Polyurethane elastomer tread chemically bonded to cast iron core.
- Offers higher weight capacities while providing good floor protection and quiet rolling operation.
- Optional precision ball bearings and tapered roller bearings require less effort to start up and maintain a rolling load; they also generate less friction heat and may prolong the life of the wheel.
- Works well in both indoor and outdoor environments; however cast iron core can rust; if this is an issue look at using aluminum or plastic core wheels.
- Durometer: 95 Shore A (+/-5).
- Temperature range: -40° F to 180° F.

Wheel Diameter	Tread Width	Hub Length	Load Capacity	Part Number <i>Replace + with Color Code</i>	Available Colors	Replace ** with desired bearing code.				
						Plain Bore	Roller Bearings	Precision Ball Bearings	Tapered Roller Bearings	Delrin Bearings
3.25	1-1/2	1-5/8	500	PU34HG**	G	84	01,03			56,57,11,12
3.25	2	2-3/16	600	PU34JG**	G	84	02,04,09,92			56,57,11,12
4	1-1/2	1-5/8	600	PU40H+**	G,V	84	01,03			56,57,11,12
4	2	2-3/16	800	PU40J+**	G,V	84	02,04,09,92	63	73	56,57,11,12
5	1-1/2	1-5/8	800	PU50H+**	G,V	84	01,03			56,57,11,12
5	2	2-3/16	1100	PU50J+**	G,V	84	02,04,09,92	63	73	56,57,11,12
5	2-1/2	2-3/4	1400	PU50KG**	G	85	23,25			58
5	3	3-1/4	1600	PU50L+**	G,V	85	24,26			58
6	1-1/2	1-5/8	800	PU60H+**	G,V	84	01,03			56,57,11,12
6	2	2-3/16	1200	PU60J+**	G,V	84	02,04,09,92	63	73	56,57,11,12
6	2	2-1/4	1200	PU60JV**	V	87	07,22			
6	2-1/2	2-3/4	1500	PU60KV**	V	84	06			56,57
6	2-1/2	2-3/4	1600	PU60K+**	G,V	85	23,25			58
6	2-1/2	3-1/4	1600	PU60Q+**	G,V	85	24,26			58
6	3	3-1/4	2000	PU60L+**	G,V	85	24,26	65		58
8	2	2-3/16	1400	PU80J+**	G,V	84	02,04,09,92	63	73	56,57,11,12
8	2	2-1/4	1400	PU80JV**	V	87	07,22			
8	2-1/2	2-3/4	1600	PU80KV**	V	84	06			56,57
8	2-1/2	2-3/4	2000	PU80K+**	G,V	85	23,25			58
8	2-1/2	3-1/4	2000	PU80Q+**	G,V	85	24,26			58
8	3	3-1/4	2500	PU80L+**	G,V	85	24,26	65		58
8	4	4-1/4	3800	PU80NG**	G	86	31,33			
10	2-1/2	2-3/4	1600	PU10KV**	V	84	06			56,57
10	2-1/2	2-3/4	2200	PU10K+**	G,V	85	23,25			58
10	2-1/2	3-1/4	2200	PU10Q+**	G,V	85	24,26			58
10	3	3-1/4	3000	PU10L+**	G,V	85	24,26	65		58
10	4	4-1/4	3200	PU10NV**	V	85	35			
12	2-1/2	2-3/4	2500	PU12K+**	G,V	85	23,25			58
12	2-1/2	3-1/4	2500	PU12Q+**	G,V	85	24,26			58
12	3	3-1/4	3500	PU12L+**	G,V	85	24,26	65		58
16	3	3-1/4	4400	PU16L+**	G,V	85	24,26			58

Bore & Bearing Sizes															
Bearing or Bore Code	02	04	06	07	09	22	23	24	25	26	31	33	35	92	
Bearing or Bore Type	Roller Bearings				Caged Roller Bearing	Roller Bearings									3/4 Roller w/Stl. Bushing
Inner Diameter	5/8	3/4	3/4	3/4	3/4	1	1	1	1-1/4	1-1/4	1-1/4	1-1/2	1	1/2	

Available Colors: Replace + in part# with Color Code.

G	V

Bearing or Bore Code	11	12	56	57	58	63	65	73	84	85	86	87	
Bearing or Bore Type	1 Piece Delrin Bearing		2 PC Delrin Bearings			Sealed Precision Ball Bearings with Top Hats		Tapered w/ top hat bushings	Plain Bore				
Inner Diameter	3/4	1/2	1/2	3/4	1	1/2	3/4	1/2	1-3/16	1-15/16	2-7/16	1-7/16	