



- Non-marking Thermoplastic rubber tread is permanently bonded to Polyolefin core.
- Shock absorbing cushioned ride offers floor protection and quiet rolling operation.
- Offers good stability at low temperatures.
- Resistant to cleaning chemicals, acids, alcohol, water, and is excellent for wash down applications & outdoor use, UV resistant.
- Flat tread wheels offer maximum durability at rated capacities; while round tread wheels offer an easy rolling ergonomic ride; reduced tread surface area also enables improved swiveling capabilities and turning mobility.
- Gray & black tread colors are available; both are non-marking.
- Durometer: 75 Shore A (+/-5).
- Temperature range: -40° F to 180° F.

Wheel Diameter	Tread Width	Hub Length	Load Capacity	Part Number <i>Replace + with Color Code</i>	Color Code	Replace ** with desired bearing code.				
						Plain Bore	Ball Bearings	Roller Bearings	Precision Ball Bearings	Delrin Bearings
2	7/8	1	75	TP20BT**		80				
2.5	1-1/4	1-9/16	250	TP25GB**			42			
3	7/8	1	125	TP30BT**		80				
3	1	1-3/16	125	TP30D+**	H, T	81			48	
3	1-1/4	1-9/16	210	TP30G+**	I	82			44	
3	1-1/4	1-9/16	210	TP30G+**	T, Y	83, 90			47	
3.5	1-1/4	1-9/16	230	TP35G+**	I	82			44	
3.5	1-1/4	1-9/16	230	TP35G+**	T, Y	83, 90			47	
4	1	1-3/16	135	TP40D+**	H, T	81			48	
4	1-1/4	1-9/16	250	TP40G+**	I	82			44	
4	1-1/4	1-9/16	250	TP40G+**	T, Y	83, 90			47	
4	1-1/2	1-5/8	280	TP40H+**	A, I	84		01,03		56,57, 11,12
4	2	2-3/16	300	TP40J+**	A, T, X, Y, Z	84		02,04,05,09, 92	60,6S,63,72	56,57, 11,12
5	1	1-3/16	135	TP50D+**	H, T	81			48	
5	1-1/4	1-9/16	300	TP50G+**	I	82			44	
5	1-1/4	1-9/16	300	TP50G+**	T, Y	83, 90			47	
5	1-1/2	1-5/8	300	TP50H+**	A, I	84		01,03		56,57, 11,12
5	2	2-3/16	350	TP50J+**	A, T, X, Y, Z	84		02,04,05,09, 92	60,6S,63,72	56,57, 11,12
6	1-1/4	1-9/16	300	TP60G+**	I	82			44	
6	1-1/4	1-9/16	300	TP60G+**	T, Y	83, 90			47	
6	1-1/2	1-5/8	375	TP60H+**	A, I	84		01,03		56,57, 11,12
6	2	2-3/16	500	TP60J+**	A, T, X, Y, Z	84		02,04,05,09, 92	60,6S,63,72	56,57, 11,12
8	1-1/2	2-1/4	400	TP80HT**	T, I	95	51, 52, 53			
8	2	2-3/16	600	TP80J+**	A, T, X, Y, Z	84		02,04,05,09, 92	60,6S,63,72	56,57, 11,12
10	2-1/2	2-3/4	1000	TP10K+**	A, I	85		23,25		58
10	3	3-1/4	1100	TP10L+**	A, I	85		24,26		58

Bearing, Hub & Thread Guard Designs



42, 51, 52, 53 Ball Bearings



44 Precision Ball Bearings



47 Precision Ball Bearings



83 Plain Bore

Bore & Bearing Sizes																	
Bearing or Bore Code:	01	02	03	04	05	09	11	12	23	24	25	26	42	48	51	52	53
Bearing or Bore Type:	Roller Bearings				S.S. Roller Bearings	Caged Roller Bearings	1 Piece Delrin Bearing		Roller Bearings				Ball Bearings	Dual Row Sealed Annular BB		Ball Bearings	
Inner Diameter:	5/8	5/8	3/4	3/4	3/4	3/4	3/4	1/2	1	1	1-1/4	1-1/4	3/8	1/2	1/2	5/8	3/4

Bore & Bearing Sizes														
Bearing or Bore Code:	56	57	60	6S	63	72	80	81	82	83	84	90	92	
Bearing or Bore Type:	2 PC Delrin Bearings		Sealed Prec. BB (Flanged)	S.S. Sealed Prec. BB (Flanged)	Prec. BB w/top hat bushings	S.S. Prec. BB w/top hat bushings	Plain Bore					83 Plain bore w/bushing	3/4 I.D. Roller w/Stl. Bushing	
Inner Diameter:	1/2	3/4	1/2	1/2	1/2	1/2	1/4	5/16	3/8	1/2	1-3/16	3/8	1/2	

