FP – FULL PNEUMATIC TIRES

WHEEL PART # EXPLANATION

FP 8 B 4 C P3

- FP: PNEUMATIC
- 8: TIRE SIZE
- B: TREAD PATTERN
- 4: PLY RATING
- C P3: BEARING CHARACTERISTIC COMBINATION

- Butyl rubber inner tube for longer air inflation
- Available in zinc, brass and different color steel rim coating
- Options of black and gray rubber tire

Tire Spec & Approx. Diameter	Tread Pattern	Ply	PSI	Hub Length	Hub Design	Hub Type	Load Cap.	Color	Part #	Replace** with desired Bearing Code. Plain Bore	Roller B	Ball B	Prec. BB
6X2	F	4	30	2-1/2	C	2	200	B/Z	FP60JB60				60
250-4 (8")	B	2	50	2-1/2	C	3	250	B/Z	FP5B1C**	95		53	P3
				3-1/4	C				FP5B2C**	95		51, 52, 53	P1, P2, P3
280-4 (8")	A	4	50	3-3/16	C	3	250	B/Z	FP8A4C**	95	38	51, 52, 53	P1, P2, P3
								B/B	FP8Z4F**				
								G/Z	FP8A4Y**				
								G/B	FP8A4R**				
				2-1/4	O			B/Z	FP8Z4O**	95		51, 52, 53	P1, P2, P3
								G/Z	FP8A4D**				
350-4 (10")	D	4	50	4	C	3	350	G/Z	FP0D4Y**	95		51, 52, 53	P1, P2, P3
									FP0D4C**	95	40	51, 52, 53	P1, P2, P3
				1.85					FP0D4SP2				
				2-1/4	O				FP0D4O**	95		51, 52, 53	P1, P2, P3
	G								FP0G4D**				
	E	4	50	2-1/4	O	1	350	B/W	FP0E4W**	95		51, 52, 53	P1, P2, P3
	C								FP0C4W**				
	C							B/G	FP0C4G**				
350-6 (12")	D	4	50	4	C	1	460	B/T	FP2D4T**	95		51, 52, 53	P1, P2, P3
	E	6	85				500		FP2E6T**				
	C	4	50				460	B/T	FP2C4T**				
480-4 (16")	C	6	75			1	650	B/T	FP6C6T**	95		51, 52, 53	P1, P2, P3
				3-3/4	C			B/B	FP6C6B65				6205
13X5.00-6		4	40	3-3/4	C	1	450	B/Z	FP13C4P2				

Tire Size Part # Abbreviations

Part # Abbrev.	Tire specification & Approximate Diameter
5	250-4 (8")
60	6"
8	280-4 (8")
0	350-4 (10")
2	350-6 (12")
13	13"
6	480-8 (16")

Wheel Characteristic Codes

Tire Color	Hub Finish	Hub Design
B=BLACK	BR=BRASS	C=CENTERED
	R=RED	
	C=CHROME	
	G=GREY	
G=GRAY	W=WHITE	O=OFFSET
	Z=ZINC	

Wheel Characteristic Combinations Part# Abbreviations

Part # Abbrev.	Code Combinations (from above table)
C	B-Z-C
G	B-G-O
D	G-Z-O
F	B-BR-C
K	B-G-C
O	B-Z-O
R	G-BR-C
T	B-W-C
W	B-W-O
Y	G-Z-C
B	B-B-C

BEARING CODES

Code	Type	Bore I. D.
95	PLAIN BORE	1-3/8
38	ROLLER BEARING	3/4
40		3/4
51	BALL BEARING	1/2
52		5/8
53		3/4
60	PRECISION BALL BEARING	1/2
P1		1/2
P2		5/8
P3		3/4
6205	SEALED PRECISION BB W/TOP HAT BUSHINGS	3/4

TREAD PATTERNS

A B C D E F G